



Bearing No.	Boundary dimensions				Basic load ratings(kN)		Limiting speeds		Mass
	mm				Dynamic	Static	rpm		Kg
	d	D	B	rs min	Cr	Cor	Grease	Oil	
24024	120	180	60	2	390	670	1,500	2,300	5.48
24024K30	120	180	60	2	390	670	1,500	2,300	5.39
24024K30W33C3	120	180	60	2	390	670	1,500	2,300	5.39
24024W33C3	120	180	60	2	390	670	1,500	2,300	5.48
24026	130	200	69	2	505	895	1,300	2,100	8.08
24026K30	130	200	69	2	505	895	1,300	2,100	7.95
24026K30W33C3	130	200	69	2	505	895	1,300	2,100	7.95
24026W33C3	130	200	69	2	505	895	1,300	2,100	8.08
24028	140	210	69	2	510	945	1,200	1,900	8.57
24028K30	140	210	69	2	510	945	1,200	1,900	8.43
24028K30W33C3	140	210	69	2	510	945	1,200	1,900	8.43
24028W33C3	140	210	69	2	510	945	1,200	1,900	8.57
24030	150	225	75	2.1	585	1,060	1,200	1,800	10.7
24030K30	150	225	75	2.1	585	1,060	1,200	1,800	10.5
24030K30W33C3	150	225	75	2.1	585	1,060	1,200	1,800	10.5

<b>24030W33C3</b>	150	225	75	2.1	585	1,060	1,200	1,800	10.7
<b>24032</b>	160	240	80	2.1	650	1,200	1,100	1,700	13
<b>24032K30</b>	160	240	80	2.1	650	1,200	1,100	1,700	12.8
<b>24032K30W33C3</b>	160	240	80	2.1	650	1,200	1,100	1,700	12.8
<b>24032W33C3</b>	160	240	80	2.1	650	1,200	1,100	1,700	13
<b>24034</b>	170	260	90	2.1	800	1,470	1,000	1,600	17.7
<b>24034K30</b>	170	260	90	2.1	800	1,470	1,000	1,600	17.4
<b>24034K30W33C3</b>	170	260	90	2.1	800	1,470	1,000	1,600	17.4
<b>24034W33C3</b>	170	260	90	2.1	800	1,470	1,000	1,600	17.7
<b>24036</b>	180	280	100	2.1	965	1,770	950	1,500	23.3
<b>24036K30</b>	180	280	100	2.1	965	1,770	950	1,500	22.9
<b>24036K30W33C3</b>	180	280	100	2.1	965	1,770	950	1,500	22.9
<b>24036W33C3</b>	180	280	100	2.1	965	1,770	950	1,500	23.3
<b>24038</b>	190	290	100	2.1	995	1,850	900	1,400	24.3
<b>24038K30</b>	190	290	100	2.1	995	1,850	900	1,400	23.9
<b>24038K30W33C3</b>	190	290	100	2.1	995	1,850	900	1,400	23.9
<b>24038W33C3</b>	190	290	100	2.1	995	1,850	900	1,400	24.3
<b>24040</b>	200	310	109	2.1	1,160	2,140	850	1,300	31
<b>24040K30</b>	200	310	109	2.1	1,160	2,140	850	1,300	30.5
<b>24040K30W33C3</b>	200	310	109	2.1	1,160	2,140	850	1,300	30.5
<b>24040W33C3</b>	200	310	109	2.1	1,160	2,140	850	1,300	31
<b>24044</b>	220	340	118	3	1,350	2,570	770	1,200	40.2
<b>24044K30</b>	220	340	118	3	1,350	2,570	770	1,200	39.6
<b>24044K30W33C3</b>	220	340	118	3	1,350	2,570	770	1,200	39.6
<b>24044W33C3</b>	220	340	118	3	1,350	2,570	770	1,200	40.2
<b>24048</b>	240	360	118	3	1,410	2,770	700	1,100	43
<b>24048K30</b>	240	360	118	3	1,410	2,770	700	1,100	42.3
<b>24048K30W33C3</b>	240	360	118	3	1,410	2,770	700	1,100	42.3
<b>24048W33C3</b>	240	360	118	3	1,410	2,770	700	1,100	43
<b>24052</b>	260	400	140	4	1,830	3,550	640	980	65.2
<b>24052K30</b>	260	400	140	4	1,830	3,550	640	980	64.1
<b>24052K30W33C3</b>	260	400	140	4	1,830	3,550	640	980	64.1
<b>24052W33C3</b>	260	400	140	4	1,830	3,550	640	980	65.2
<b>24056</b>	280	420	140	4	1,950	3,950	590	900	69
<b>24056K30</b>	280	420	140	4	1,950	3,950	590	900	67.9
<b>24056K30W33C3</b>	280	420	140	4	1,950	3,950	590	900	67.9
<b>24056W33C3</b>	280	420	140	4	1,950	3,950	590	900	69

<b>24060</b>	300	460	160	4	2,450	4,950	540	840	98
<b>24060K30</b>	300	460	160	4	2,450	4,950	540	840	96.4
<b>24060K30W33C3</b>	300	460	160	4	2,450	4,950	540	840	96.4
<b>24060W33C3</b>	300	460	160	4	2,450	4,950	540	840	98