



Bearing No.	Boundary dimensions				Basic load ratings(kN)		Limiting speed		Mass
	mm				Dynamic	Static	rpm		
	d	D	B	r _{smin}	Cr	Cor	Grease	Oil	
1200	10	30	9	0.6	5.5	1.19	21,000	24,000	0.033
1201	12	32	10	0.6	5.6	1.27	18,000	22,000	0.04
1202	15	35	11	0.6	7.45	1.75	16,000	19,000	0.049
1203	17	40	12	0.6	7.9	2.01	14,000	17,000	0.072
1204	20	47	14	1	9.9	2.61	13,000	15,000	0.116
1204K	20	47	14	1	9.9	2.61	13,000	15,000	0.114
1205	25	52	15	1	12.1	3.3	11,000	13,000	0.138
1205K	25	52	15	1	12.1	3.3	11,000	13,000	0.135
1206	30	62	16	1	15.6	4.65	9,200	11,000	0.217
1206K	30	62	16	1	15.6	4.65	9,200	11,000	0.213
1207	35	72	17	1.1	15.8	5.1	8,000	9,400	0.317
1207K	35	72	17	1.1	15.8	5.1	8,000	9,400	0.312
1208	40	80	18	1.1	19.3	6.55	7,100	8,400	0.414

1208K	40	80	18	1.1	19.3	6.55	7,100	8,400	0.407
1209	45	85	19	1.1	21.9	7.35	6,400	7,500	0.457
1209K	45	85	19	1.1	21.9	7.35	6,400	7,500	0.448
1210	50	90	20	1.1	22.7	8.1	5,800	6,800	0.515
1210K	50	90	20	1.1	22.7	8.1	5,800	6,800	0.504
1211	55	100	21	1.5	26.8	10	5,300	6,200	0.692
1211K	55	100	21	1.5	26.8	10	5,300	6,200	0.679
1212	60	110	22	1.5	30	11.5	4,900	5,800	0.879
1212K	60	110	22	1.5	30	11.5	4,900	5,800	0.864
1213	65	120	23	1.5	31	12.5	4,500	5,300	1.13
1213K	65	120	23	1.5	31	12.5	4,500	5,300	1.11
1214	70	125	24	1.5	34.5	13.8	4,200	4,900	1.24
1215	75	130	25	1.5	39	15.7	3,900	4,600	1.33
1215K	75	130	25	1.5	39	15.7	3,900	4,600	1.31
1216	80	140	26	2	40	17	3,700	4,300	1.65
1216K	80	140	26	2	40	17	3,700	4,300	1.62
1217	85	150	28	2	49	20.8	3,500	4,100	2.06
1217K	85	150	28	2	49	20.8	3,500	4,100	2.03
1218	90	160	30	2	57	23.5	3,300	3,800	2.51
1218K	90	160	30	2	57	23.5	3,300	3,800	2.47
1219	95	170	32	2.1	64	27.1	3,100	3,600	3.1
1219K	95	170	32	2.1	64	27.1	3,100	3,600	3.05
1220	100	180	34	2.1	69	29.7	2,900	3,400	3.7
1220K	100	180	34	2.1	69	29.7	2,900	3,400	3.64
1221	105	190	36	2.1	74.5	32.5	2,800	3,300	4.34
1222	110	200	38	2.1	80.5	35.5	2,600	3,100	5.15
1222K	110	200	38	2.1	80.5	35.5	2,600	3,100	5.07